












www.srdinfotech.com
 Skype: [srdinfotech](https://www.skype.com/add?contact=srdinfotech)
info@srdinfotech.com
 +919820429309

Product Guide

	High Temperature and Rugged Line				Embeddable Line for Source Tagging and Extreme Conditions			Extra Small Line	
Series	X II Series				iN Series			XS Series	
Product	 Micro ^{II}	 Nano ^{II}	 Pico ^{II} / Pico ^{II} Plus	 Pico-On Plus	 Micro-iN	 Nano-iN	 Pico-iN / Pico-iN Plus	 Dash-iN XS / Dash-On XS	 Dot-iN XS / Dot-On XS
Operating frequency	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]	902-928 MHz [US] 866-868 MHz [EU]
IC type	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3
Memory configuration	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)
Read range on metal	Up to 33 ft (10 m)	Up to 20 ft (6 m)	Up to 6.6 ft (2 m); 10 ft (3 m) for Pico ^{II} Plus	Up to 10 ft (3 m)	Up to 20 ft (6 m) when embedded	Up to 13 ft (4 m) when embedded	Up to 3.3 ft (1 m); 6.6 ft (2 m) for Pico-iN Plus when embedded	Up to 6.6 ft (2 m); 5 ft (1.5 m) when embedded	Up to 5 ft (1.5 m); 3 ft (1 m) when embedded
Read range off metal	Limited	Limited	Limited	Limited	Limited	Limited	Limited	Limited	Limited
Case material	Engineering grade nylon polymer	Engineering grade nylon polymer	Engineering grade nylon polymer	Ceramic	Ceramic	Ceramic	Ceramic	Ceramic	Ceramic
Mounting system	Rivet hole, ø 0.12 in (3.2 mm); adhesive (optional)	High performance adhesive	High performance adhesive	High performance adhesive	Embedded	Embedded	Embedded	Epoxy, embedded	Epoxy, embedded
Operating temperature	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)
Application temperature	-40°F (-40°C) to +482°F (+250°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)	-40°F (-40°C) to +302°F (+150°C)
Compression strength	181 psi (1259 kPa)	166.8 psi (1150 kPa)	174 psi (1200 kPa)	170 psi (1176 kPa)	Packaging dependent	Packaging dependent	Packaging dependent	Packaging dependent	Packaging dependent
IP classification	IP68	IP68	IP68	IP68	IP68	IP68	IP68	IP68	IP68
Dimensions	2.01 x 1.43 x 0.30 in (51 x 36.3 x 7.5 mm)	1.25 x 0.51 x 0.19 in (31.7 x 12.8 x 4.8 mm)	0.70 x 0.43 x 0.19 in (17.7 x 10.9 x 4.8 mm)	0.47 x 0.28 x 0.12 in (12 x 7 x 3 mm)	1.18 x 1.18 x 0.12 in (30 x 30 x 3 mm)	0.98 x 0.35 x 0.12 in (25 x 9 x 3 mm)	0.47 x 0.28 x 0.12 in (12 x 7 x 3 mm)	0.48 x 0.12 x 0.09 in (12.3 x 3 x 2.2 mm)	ø 0.24 x 0.1 in (ø 6 x 2.5 mm)
Weight	0.92 oz (26 g)	0.18 oz (5 g)	0.07 oz (2 g)	0.05 oz (1.4 g)	0.49 oz (14 g)	0.13 oz (3.6 g)	0.05 oz (1.4 g)	0.016 oz (0.44 g)	0.012 oz (0.34 g)
Sample applications	Bulk container tracking, vehicle tracking, post-paint oven baking, autoclave	Tool tracking, WIP conveying equipment, IT/telecom management, instrument tracking, weapons tracking	Tool tracking, weapon tracking, medical device management, instrument tracking	Tool tracking, electronic device management, instrument tracking	Reusable container logistics, heavy machinery tracking, automotive parts identification	IT asset identification, weapons tracking, tool management	IT and laptop tracking, tool tracking, embedded bolt identification, weapons tracking	Instrument tracking, tool tracking, medical device management, source tagging	Instrument tracking, tool tracking, medical device management, source tagging



www.srdinfotech.com
 Skype: [srdinfotech](https://www.skype.com/partners/srdinfotech)
info@srdinfotech.com
 +919820429309

verify. quantify. XERAFY™

Product Guide

Series	Versatile On and Off Metal Line				Specialty Tag Line		High Memory Line		Flexible Metal Line
	Trak Series				Specialized Series		XL Series		Metal Skin™ Series
Product									
	Cargo Trak	Versa Trak	Data Trak	Global Trak	Bric	Xylinder	Sky-ID™	Pico XL	Metal Skin Mercury
Operating frequency	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	860-960 MHz (Global)	902-928 MHz (US) 866-868 MHz (EU)	902-928 MHz (US) 866-868 MHz (EU)	860-960 MHz (Global)	860-960 MHz (Global)	860-960 MHz (Global)
IC type	Alien Higgs-3	Alien Higgs-3	Alien Higgs-3	Impinj Monza 4QT/M4	Alien Higgs-3	Alien Higgs-3	Tegochip XL	Tegochip XL	Impinj Monza 4QT/M4
Memory configuration	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	128 EPC bits	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 480 bits (512 bit user memory)	96 EPC bits, extendable to 224 bits (4k byte user memory) or 496 bits (8k byte user memory)	96 EPC bits, extendable to 496 bits (2k bit user memory)	128 EPC bits
Read range on metal	Up to 39 ft (12 m)	Up to 26 ft (8 m)	Up to 13 ft (4 m)	Up to 8 ft (2.5 m)	Up to 19 ft (6 m)	Up to 19 ft (6m)	Up to 4 ft (1.2 m)	Up to 1 ft (0.3 m)	Up to 13 ft (4 m)
Read range off metal	Up to 20 ft (6 m)	Up to 13 ft (4 m)	Up to 6.6 ft (2 m)	Up to 6 ft (1.8 m)	Up to 13 ft (4 m); 6.5 ft (2 m) when embedded 2 in (50 mm) in concrete	Limited	Limited	Limited	Up to 16 ft (5 m)
Case material	ABS plastic	ABS plastic	ABS plastic	Polycarbonate	Engineering grade nylon polymer	Engineering grade nylon polymer	Engineering grade polyester FR-4	Engineering grade nylon polymer	Not applicable
Mounting system	Rivet hole, ø 0.14 in (3.5 mm); adhesive (optional)	High performance adhesive	Adhesive; built-in ø 0.05 in (1.2 mm) tethering hole	Adhesive; built-in ø 0.1 in (2.6 mm) tethering hole	Mounted or embedded in concrete	High performance adhesive	High performance adhesive	High performance adhesive	High performance adhesive (dry)
Operating temperature	-40°F (-40°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-22°F (-30°C) to +185°F (+85°C)	-40°F (-40°C) to +185°F (+85°C)	-40°F (-40°C) to +185°F (+85°C)	-40°F (-40°C) to +185°F (+85°C)	+32°F (0°C) to +158°F (+70°C)	+32°F (0°C) to +158°F (+70°C)	-40°F to +185°F (-40°C to +85°C)
Application temperature	-40°F (-40°C) to +185°F (+85°C)	-40°F (-40°C) to +185°F (+85°C)	-40°F (-40°C) to +185°F (+85°C)	-40°F (-40°C) to +185°F (+85°C)	-40°F to +194°F (-40°C to +90°C)	-40°F to +302°F (-40°C to +150°C)	-67°F (-55°C) to +302°F (+150°C)	-67°F (-55°C) to +302°F (+150°C)	-40°F to +185°F (-40°C to +85°C)
Compression strength	29 psi (200 kPa)	26.1 psi (180 kPa)	14.5 psi (100 kPa)	14.5 psi (100 kPa)	93 psi (641 kPa)	80 psi (551 kPa)	203 psi (1400 kPa)	174 psi (1200 kPa)	Not applicable
IP classification	IP68	IP54	IP54	IP54	IP68	IP68	IP68	IP68	Not applicable
Dimensions	3.94 x 1.02 x 0.35 in (100 x 26 x 8.9 mm)	1.97 x 0.67 x 0.20 in (50 x 17 x 5 mm)	1.45 x 0.51 x 0.12 in (36.7 x 13 x 3 mm)	1.50 x 0.51 x 0.15 in (38 x 13 x 3.8 mm)	2.75 x 1.25 x 0.43 in (70 x 32 x 11 mm)	ø 1.26 x 0.25 in (ø 32 x 6.5 mm)	1.39 x 0.80 x 0.17 in (35.2 x 20.2 x 4.4 mm)	0.70 x 0.43 x 0.19 in (17.7 x 10.9 x 4.8 mm)	3.58 x 1.18 x 0.027 in (91 x 30 x 0.66 mm) dry; 4 x 1.5 x 0.031 in (101.6 x 38 x 0.76 mm) Smart Label
Weight	0.61 oz (17.2 g)	0.11 oz (3 g)	0.07 oz (2 g)	0.09 oz (2.6 g)	0.85 oz (24 g)	0.26 oz (7.4 g)	0.21 oz (6 g)	0.07 oz (2 g)	0.07 oz (2 g)
Sample applications	Vehicle chassis and trailer tracking, Unit Load Device identification, yard management	Instrument tracking, pallet tracking, RTI management, storage rack identification	IT asset management, laptop and PC security, WIP small parts bins, instrument tracking	Global supply chain logistics, IT asset management, datacenter servers	Facility management, yard management, work in progress	Gas cylinder tracking, container management, smart grid identification, ATEX certified	SAE AS5678 and ATA Spec2000 compliant, aircraft parts, configuration management, MRO management	Aircraft parts maintenance, IT management, MRO management	Product authentication, laptop tracking, global supply chain management, cylinder tracking, foil-based packaging