

COMPETITIVE FEATURES, BEST PRICED 4 IPS THERMAL TRANSFER PRINTER IN THE WORLD.

TTP-244 DESKTOP THERMAL TRANSFER BAR CODE PRINTER

The new TSC™ TTP-244 thermal transfer bar code printer is a robust label printer. It is designed to provide labeling solutions for customer who simply needs to print labels and tags at the lowest cost.

It re-defines low volume desktop bar code printing. With the largest media/ribbon capacities, fast print speed, and large memory capacity in its class, the TTP-244 outperforms the competition easily. These virtually trouble free units feature a standard two-year warranty. Once you plug it in, you won't have to worry about it.

The TTP-244 is based on the best selling TTP-243 platform, features such as legendary Dual-Motor design, and industrial standard media capacity. With its small, compact footprint, it is perfect for a variety of label and tag printing applications. The TTP-244 can print a wide variety of labels ranging from low volume shipping labels to compliance and general purpose product identification labels and tags.

Other applications include automobile service shops, walk-in shipping and mail centers, and inventory control for stock rooms. And with PDF417 and MaxiCode two dimensional bar code capabilities, the TTP-244 can print complex transportation formats.

The TTP-244 offers the following features:

- ▶ 2 MB DRAM, 2MB FLASH memory
- ▶ Dual-Motor gear driven design
- ▶ 300 meter ribbon supply on 1" core (coated side out)
- ▶ 4.3" OD internal media supply, optional 8.4" OD external media holder
- ▶ 4 inches per second print speed
- ▶ Serial & USB interfaces
- ▶ Free bundled labeling software



Value . Performance . Support

TTP-244

DESKTOP THERMAL TRANSFER BAR CODE PRINTER

SPECIFICATIONS

Printer model	TTP-244
Resolution	203 DPI
Printing method	Thermal Transfer
Print speed	Up to 4 ips
Max. print width	104 mm (4.09")
Max. print length	1016 mm (40")
Enclosure	ABS plastic
Physical dimension	288 mm (L) x 232 mm (W) x 156 mm (H) 11.34" (L) x 9.13" (W) x 6.14" (H)
Ribbon capacity	300 m (984 ft.), 1" core, Max. OD 67 mm
Label roll capacity	109.2 mm (4.3") OD
Processor	32-bit RISC CPU
Memory	<ul style="list-style-type: none">• 2MB Flash memory• 2MB DRAM
Interface	<ul style="list-style-type: none">• Standard RS-232 (max. 19,200 bps)• USB 1.1 or Centronics (factory option)
Power	AC input: 100-240V universal switching power supply DC output: 24V 2A
Operation switch, button	<ul style="list-style-type: none">• One power switch• Feed button and Pause button
Sensors	<ul style="list-style-type: none">• Transmissive sensor• Reflective sensor• Ribbon end sensor
Internal font	8 alpha-numeric bitmap fonts, one true type font-CG triumvirate bold condensed
Code Page	<ul style="list-style-type: none">• Codepage 850 (Latin 1)• Codepage 852 (Latin 2)• Codepage 860 (Portuguese)• Codepage 863 (French Canadian)• Codepage 865 (Nordic)• Codepage 857 (Turkish)• Codepage 861 (Iceland)• Codepage 1252 (Latin 1)• Codepage 1250 (Latin 2)• Codepage 1254 (Turkish)• Latin-1 (ISO-8859-1: Western European)• Latin-2 (ISO-8859-2: Central European)• Latin-9 (ISO-8859-9: Turkish)
Bar code	1D bar code Code 39, Code 39C, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, ITF 14, EAN 14 2D bar code PDF-417, Maxicode, DataMatrix, QR code
Font & barcode rotation	0, 90, 180, 270 degrees
Printer language	<ul style="list-style-type: none">• TSPL2• TSPL-EZ
Media type	Continuous, die-cut, Fan-fold, black mark, tag
Media wound type	Outside wound
Media width	25.4~114mm (1.0" ~ 4.4")
Media thickness	0.06~0.25 mm (2.36~9.84 mil)
Media core diameter	25.4~76.2 mm (1"~3")
Label length	10 mm (0.4")~1016 mm (40")
Environment condition	Operation: 5~40°C(41°F~104°F), 25~85% non-condensing Storage: -40~60°C(-40°F~140°F), 10~90% non-condensing
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, BSMI Class A, TUV/GS, CCC
Accessories	<ul style="list-style-type: none">• BarTender UltraLite Edition Labeling software CD disk• Quick start guide• External auto switching power supply• Power cord• Label Spindle, fixing tab x2• Ribbon spindle x2• Ribbon rewind spindle paper core
Limited warranty	<ul style="list-style-type: none">• Printer: 2 years• TPH: 1 million inches or 12 months which comes first since delivery from TSC• Platen: 50 km
Factory option	<ul style="list-style-type: none">• On board secondary Flash 2MB• Centronics Parallel port (SPP mode)
User option	<ul style="list-style-type: none">• Keyboard display unit (KU-007 Plus and KP-200)• External Ethernet print server• External wireless (802.11b/g) print server• External roll mount, media OD 214 mm (8.4") with 1" or 3" core• 3" core label spindle• Contact CCD bar code scanner• Long range linear image bar code scanner• Battery pack

