

AB-88K



- High speed

The high performance thermal printer AB-88K suitable for any moving retail or hospitality environment. It prints at a staggering 150mm per second without the distracting noise associated with impact printers.

- Drop-in-paper loading

A simple drop-in-paper loading means that even inexperienced operators can load paper rolls with the minimum of effort.

- Black mark orientation

Print with fixed length, the black mark sensor orientates to print fixed length.




Features




Technical specifications

Print method	Thermal line printing
Print font	12x24
Column	56columns
Character per line	48
Print speed	150mm/s
Paper supply method	Easy paper loading
Resolution	203DPI (8 dots/mm)
Data buffer	4KB
Emulation	ESC/POS
Interface	RS-232,parallel(option)
Paper dimensions	Max ø83.0mm
Paper width	79.5±0.5mm
Paper thickness	0.06 to0.07mm
Power supply	24VDC±10%
Power consumption	Approx.1.8A(mean)
MCBF	52,000,000
Drawer port	1port
Operation Temp	0-45°C
Auto cutter(option)	Full cut
Auto cutter MCBF	1,500,000 cuts

A. Remove the used paper roll core if there is one.



B. Insert the paper roll as shown.




C. Pull out a small amount of paper, as shown. Then close the cover.



AB-88K Mini Thermal Printer

- High speed
- Drop-in-paper loading
- Black mark orientation



SP TRADERS
SRD Infotech Pvt.Ltd.

C/2, Avanti Apartment, L.M. Road, Navagaon,
Dahisar-(W), Mumbai-400 068.

Mobile: 9820429309 / 9321026721

Ring: +91-022 28950137

E_MAIL: sptraders99@rediffmail.com
info@srinfotech.com

www.srdinfotech.com