

# Magellan® 1000i

Omnidirectional Imaging Scanner

## Data Sheet



Shown with Optional Tilting Riser Stand

### Features:

- Aggressive imaging performance on 1D and 2D bar codes speeds checkout for better customer service
- New imaging technology eliminates moving parts associated with laser scanners for improved reliability
- Hands-free scanning for small, easily handled items, handheld scanning for bulkier items
- Precise imaging scan volume eliminates misreads caused by stray laser scan lines
- Small footprint and size allow for easy integration into point-of-sale and OEM applications
- Textured grip area and small size allow hands of all sizes to comfortably hold the scanner when needed
- Checkpoint® Systems EAS compatible
- Optional targeted scanning mode for PLU Lists
- Optional tilting stand allows scan volume to be optimized for each user and has screw holes for fixed mounting
- Standard product is available in either Black or Grey. Other colors and custom logo options are available for a minimum quantity purchase. Please contact Datalogic Scanning or your Datalogic Scanning reseller for more information on this service.

### Accessories:

- Tilting Riser Stand
- Fixed Mounting Plate
- Gooseneck Stand (23 cm / 9 in)

### Mechanical

Dimensions	Scanner	Stand	Scanner with Stand
Height	8.3 cm / 3.3 in	5.8 cm / 2.3 in	14.0 cm / 5.5 in
Width	7.1 cm / 2.8 in	7.4 cm / 2.9 in	7.4 cm / 2.9 in
Length	9.5 cm / 3.7 in	9.7 cm / 3.8 in	9.7 cm / 3.8 in
Weight	198 g / 7.0 oz	187 g / 6.6 oz	385 g / 13.6 oz

### Environmental

#### Temperature Rating

**Operating:** 0 to 40 °C / 32 to 104 °F

**Storage/Transport:** -40 to 70 °C / -40 to 158 °F

**Humidity:** 5 to 95% NC (non-condensing)

**Shock:** Multiple 1.2 m / 4 ft drops

**Water & Dust Resistance:** IP52

### Electrical

#### Operating Voltages

5.0V model ±10%

8.0 - 14.0V model

**Operating Current (idle):** < 300 mA

**Operating Current (label read):** < 400 mA

### Communications

- RS-232
- USB
- IBM USB
- Keyboard Wedge
- Wand Emulation
- IBM 46xx / RS-485

### Optical

**Scan Pattern:** 104 line

**Scan Rate:** 1170 digital scan lines/second

**Single Line Activation:** Optional Button

**Scan Volume:** 987 cm<sup>3</sup> / 60 in<sup>3</sup>

**Minimum Resolution:** 5 mil

**Print Contrast:** 25%

**Roll:** 0 - 360°

**Pitch:** ±65°

**Yaw:** ±75°

#### Ambient Light

**Indoor:** < 6,000 Lux / 557 foot candles

**Outdoor:** < 86,100 Lux / 7,999 foot candles

**Depth of Field:** Please refer to table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	RANGE
5 mil	0.64 - 4.45 cm / 0.50 - 1.75"
7.5 mil	0.64 - 5.72 cm / 0.25 - 2.25"
10 mil	0 - 12.7 cm / 0 - 5"
13 mil UPC	0 - 15.2 cm / 0 - 6"
20 mil	0 - 17.5 cm / 0 - 6.75"

Minimum distance determined by symbol length and scan angle.  
Printing resolution, contrast, and ambient light dependent.

### Decoding Capability

The Magellan® 1000i autodiscriminates between the following supported symbologies:

#### Retail Codes:

- UPC Versions A&E
- UPC Supplementals (Bookland and Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 and C128)
- GS1 DataBar™ (RSS): Omnidirectional, Stacked Omnidirectional, Expanded, Expanded Stacked and Limited
- EAN 8 and 13 with full expansion 8 to 13
- JAN 8 and 13 with full expansion 8 to 13
- EAN/JAN two label
- UCC/EAN 128
- Italian Pharmacode
- Supports GTIN

#### Industrial Codes:

- Code 39 (with full ASCII)
- Code 128 (Up to 80 characters, including Code 39 conversions)
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Codabar
- MSI/Plessey

#### Optional 2D Codes:

- PDF417
- Data Matrix (ECC 200)

#### Optional Image Capture:

- JPG image capture feature up to 752 x 480 resolution

Please contact your Datalogic Scanning representative for other available symbologies.

### Safety and Regulatory

**Electrical:** Gost R; TÜV; UL; cUL; NOM

**Emissions:** Complies to FCC; EN 55022; AS/NZS CISPR 22; VCCI; CNS 13438; ICES-005

**Restriction of Hazardous Substances:** Complies to EU RoHS



### Other

**EAS compatibility:** Integrated EAS hardware works with Checkpoint® Systems.



## DATALOGIC™

Datalogic Scanning, Inc.

**SP TRADERS**  
**SRD Infotech Pvt.Ltd.**

C/2, Avanti Apartment, L.M.Road, Navagaon,  
Dahisar-(W), Mumbai-400 068.

Mobile: +919820429309 / +919321026721

Ring: +91-022 28950137

E\_MAIL: [info@srdinfotech.com](mailto:info@srdinfotech.com) ;  
[spraders99@rediffmail.com](mailto:spraders99@rediffmail.com)

[www.srdinfotech.com](http://www.srdinfotech.com)



Regional restrictions apply to some optional features.

Copyright © Datalogic Scanning, Inc. 2005-2008. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic SpA. • Magellan is registered trademarks of Datalogic Scanning Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site [www.scanning.datalogic.com](http://www.scanning.datalogic.com). • Product specifications are subject to change without notice.