

Magellan® 1400i

Omni-Directional Imaging Scanner



Features:

- Aggressive imaging performance and intuitive operation reduces checker training and speeds checkout for better customer service
- Autodiscriminates PDF and ID bar codes
- New imaging technology eliminates moving parts associated with laser scanners for improved reliability
- Targeted scanning mode for PLU Lists
- Hands-free scanning for small, easily handled items, handheld scanning for bulkier items
- Precise imaging scan volume eliminates misreads caused by stray laser scan lines
- Small footprint and size allow for easy integration into point-of-sale
- Textured rubber grip area and small size allow hands of all sizes to comfortably hold the scanner when needed
- Checkpoint® Systems EAS compatible
- Tilting stand allows scan volume to be optimized for each user and has screw holes for fixed mounting
- Standard product is available in either Black or Light Grey. Other colors and custom logo options are available for a minimum quantity purchase. Please contact Datalogic Scanning or your Datalogic Scanning reseller for more information on this service.

Mechanical

Dimensions (Scanner with Stand):

Height: 181 cm / 71.3"
Width: 8.2 cm / 3.23"
Length: 9.7 cm / 3.82"

Weight: 3454 g / 15.7 oz

Environmental

Temperature Rating

Operating: 0° to 40° C / 32° to 104° F
Storage/Transport: -40° to 70° C / -40° to 158° F

Humidity: 5 to 95% NC (non-condensing)

Shock: Multiple 1.2 m / 4' drops

Water & Dust Resistance: IP52

Electrical

Operating Voltages

5.0V model ± 5%
8.0 – 14.0V model

Operating Current (idle): < 350mA

Operating Current (label read): < 450mA

Communications

- RS-232
- USB
- OEM USB
- Keyboard Wedge
- Wand Emulation
- IBM 46xx / RS-485

Optical

Scan Pattern: 100 line

Scan Rate: 1,100 (digital scan lines/second)

Single Line Activation: via button

Scan Volume: 1311 cm³ / 80 in³

Minimum Resolution: 5 mil

Print Contrast: 25%

Roll: 0 – 360°

Pitch: ±65°

Yaw: ±75°

Ambient Light

Indoor: < 557 foot candles / 6,000 Lux

Outdoor: < 7,999 foot candles / 86,100 Lux

Depth of Field: Please refer to table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	RANGE
5 mil	19 to 50 cm / 0.75 to 2.0"
6.6 mil (PDF)	3.8 to 7.6 cm / 1.5 to 3.0"
7.5 mil	1.3 to 10.2 cm / 0.5 to 4.0"
10 mil	0 to 15.2 cm / 0 to 6.0"
10 mil (PDF)	3.1 to 17.7 cm / 1.25 to 7.0"
13 mil (UPC)	0 to 20.3 cm / 0 to 8.0"
15 mil (PDF)	2.5 to 20.3 cm / 1.0 to 8.0"
20 mil	0 to 22.9 cm / 0 to 9.0"

Minimum distance determined by symbol length and scan angle.
Printing resolution, contrast, and ambient light dependent.

Data Sheet

Decoding Capability

The Magellan® 1400i omnidirectional imaging scanner autodiscriminates between the following supported symbologies:

Retail Codes:

- EAN 8 & 13 with full expansion 8 to 13
- EAN/JAN two label
- JAN 8 & 13 with full expansion 8 to 13
- UCC/EAN 128
- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI28)
- Dual Bar Codes for Japan (2 label read)
- Italian Pharmacode
- PDF-417/Micro-PDF
- Reduced Space Symbology (RSS): RSS-14, RSS expanded, RSS Stacked (omni-directional), RSS Composites and RSS Limited
- Supports GTIN

Industrial Codes:

- Code 39 (with full ASCII)
- Code 128 (Up to 80 characters, including Code 39 conversions)
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Codabar
- MSI/Plessey

Please contact your Datalogic Scanning representative for other available symbologies.

Safety and Regulatory

Electrical: Gost R; TÜV; UL; cUL; NOM

Emissions: Complies to FCC; EN 55022; AS/NZS CISPR 22; VCCI; CNS 13438; ICES-003

Restriction of Hazardous Substances: Complies to EU RoHS



Other

EAS Compatibility: Integrated EAS hardware works with Checkpoint® Systems.

DATALOGIC™

Datalogic Scanning, Inc.

Toll free: 1 800 695 5700

International: 1 541 683 5700

E-mail us at: scanning@datalogic.com

www.datalogic.com



Copyright © Datalogic Scanning, Inc. 2005-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. - Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. - The Datalogic logo is a trademark of Datalogic S.p.A. - Magellan is registered trademarks of Datalogic Scanning Inc. - All other brand and product names are trademarks of their respective owners. - Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.datalogic.com. - Product specifications are subject to change without notice.

R40-0164-UK US-B 0207