Accelerate Enterprise Productivity BIP-5000



حاصاما

BIP-5000

INDUSTRIES











Retail

Public Transport

Hospitality

Healthcare

Finance

KEY FEATURES & BENIFITS

Functionality



1D/2D Barcode, Quadband, WiFi

BIP-5000 is the AutoID PDA integrated with Barcode Scanner as well as Voice and Data Communication and WLAN. The ability to collect barcode data and transfer data with high-speed in a single device improves field force automation and increases productivity.

Rugged



IP65, 1.5m Drop, -20°C to 55°C

BIP-5000 is built to withstand harsh work environments.

- Rated IP65 for protection against rain and dust
- Withstand multiple 1.5m drops to concrete
- Operate in a temperature range of -20°C to 55°C

Compatibility



Windows Mobile or Windows CE

BIP-5000 with Windows Mobile-based operating system makes it easy to install custom applications and access to your work PC. The device allows you to manage real-time information all about work documents, customers, inventory, delivery and much more without any restraints of time or place.

Ergonomic



3.5" Touch Screen, Numeric Keypad

- 3.5" display delivers excellent graphic capability and readability.
- Touch screen and numeric keypad provides simple and easy operation.
- Sleek, compact and hand-held device grants you easy control of your work with one hand on the go.



Warehousing



Field Force Automation







Construction

Government/Public Sector

APPLICATIONS





















Parcel Delivery Meter Reading Public Safety

Patient/Pharm

Work Order Tracking

Logistics

Management

Customer Management

Management

Inventory Management

Facility Management



BIP-5000

SPECIFICATIONS	BIP-5000	BIP-5300
PHYSICAL CHARACTERISTICS		
DIMENSIONS (W x H x D)	75 x 150.3 x 24.9mm / 3.0 x 5.9 x 1.0 inch	
WEIGHT	Excluding battery: 253g / Including standard battery: 314g / Including extended battery: 347g	
DISPLAY	3.5" QVGA with backlight, TFT-LCD, 260K, 240 x 320	
TOUCH PANEL	Analog resistance type	
KEYPAD	Numeric keypad	
STANDARD BATTERY	Rechargeable, 3.7V, 2000mAh, Li-polymer	
EXTENDED BATTERY (optional)	Rechargeable, 3.7V, 4000mAh, Li-polymer	
EXPANSION SLOT	Customer-accessible MiniSD slot for removable memory cards up to 2G	
SIM SLOT	1 SIM	
AUDIO	Speaker, Headset jack	
CAMERA	2 megapixel color camera with LED flash	
GPS	Support (vehicle GPS cradle)	
PERFORMANCE CHARACTERISTICS		
CPU	PXA 270, 520MHz	
OS	Windows Mobile 5.0 / Windows Mobile 6.0 (optional)	Windows CE 5.0
MEMORY	128MB RAM / 128MB ROM (up to 256MB)	
INTERFACE	RS-232C, USB 1.1 Host & Client	RS-232C, USB 1.1 Client
USER ENVIRONMENT CHARACTERISTICS		
OPERATING TEMP	-20℃ to 55℃ / -4°F to 131°F	
STORAGE TEMP	-25℃ to 70℃ / -13°F to 158°F	
HUMIDITIY	93% non-condensing	
DROP SPEC	5 ft./1.5m drop to steel surface, 2 drops per 6 sides	
RAIN/DUST PROTECTION	IP65	
INTEGRATED RADIO		
WWAN RADIO	GSM/GPRS/EDGE (Quadband: 850/900/1800/1900MHz)	CDMA 1x/EvDO (Dualband: 800/1800MHz)
WLAN RADIO	IEEE 802.11b/g	IEEE 802.11a/b/g
WPAN RADIO	Bluetooth Class V1.2, IrDA 1.2	
DATA CAPTURE		
TYPE	1D&PDF417 Laser Class II or 1D&2D CMOS Imager	

















ACCESSORIES

















Cradle

Battery

Protection Film

Adapter

Power Cable

USB Cable

Stylus Pen

Bluebird



C/2, Avanti Apartment, L.M.Road,Navagaon, Dahisar-(W), Mumbai-400 068. Mobile: +919820429309 / +919321026721 Ring: +91-022 28950137 E_MAIL: info@srdinfotech.com; sptraders99@rediffmail.com